STONEWAYS VPRS

2024 Rating Certificate

Yacht	Petasu	s		Rig	Berm	udian Sloop			
Sail number	GBR12	93L		Design	Elan 3	87			
тсс	0.989			Series / built	2003				
TCC 2	0.951	with no dowr	nwind H/S	Crew limit	9	people			
Performance indicators									
Mainsail area	35.40	m ²	Miz	zen / mizzen staysail area	0.00	m ² /	0.00 m ²		
Upwind headsail area	38.30	m^2		Displacement / length	207				
Flying headsail area	0.00	<i>m</i> ²		Sail area / wetted surface	2.50	(upwind sails)			
Spinnaker area	87.90	m ²		Sail area / displacement		(upwind sails)			
Hull & appendages			source	Rig			source		
Hull Length	LH	11.16 m	D	Spar material		Aluminiur	n alloy		
Bow overhang	BO	0.42 m	E	Forestay length	FL	14.95 m	E		
Stern overhang	SO	0.84 m	А	Foretriangle base	J	4.20 m	Р		
Waterline length	LWL	9.90 m	С	Flying h/sail tack length	FHTL	m			
Stern height	Y	0.17 m	А	Spinnaker pole length	SPL	4.20 m	0		
Beam	MB	3.65 m	Р	Mainsail hoist	P	13.65 m	А		
Topside overhang	TSO	0.33 m	А	Mainsail outhaul	E	4.82 m	А		
Freeboard at mast	FBI	1.15 m	E	Boom above sheer	BAS	1.37 m	E		
Draught	т	2.34 m	D	Mizzen hoist	PY	m			
Empty weight	EW	6642 kg	А	Mizzen outhaul	EY	m			
Fixed ballast weight	KW	2190 kg	Р	Main sail					
Moveable ballast		None		Half width	мнw	2.71 m	0		
Keel type		H2H5L1N1		Three quarter width	MTW	1.47 m	0		
Keel depth	KD	1.79 m	0	Upper width	MUW	0.77 m	0		
Keel chord	КС	1.06 m	0	Construction		Woven			
Rudder type		Spade		Reefing		Slab			
Rudder depth	RD	1.80 m	0	Upwind headsail					
Rudder chord	RC	0.45 m	0	Luff length	HLU	14.10 m	0		
Propeller type		Folding		Luff perpendicular	HLP	5.55 m	0		
Propeller blades	PRN	2		Half width	HHW	2.67 m	0		
Propeller diameter	PRD	0.41 m	0	Three quarter width	HTW	1.31 m	0		
Mizzen staysail				Foot height	HFH	0.48 m	0		
Staysail luff length	LLY	т		Construction		Woven			
Staysail luff perp	LPY	m		Reefing		Roller			
Flying headsail (down	wind hea	dsail)	Spinnaker (downwind	headsai	I)				
FH luff length	FHLU	т		* Luff length	SLU	14.12 m	А		
FH leech length	FHLE	m		* Leech length	SLE	14.12 m	А		
FH half width	FHHW	m		* Half width	SHW	7.60 m	А		
FH foot width	FHFL	m		* Foot width	SFL	7.10 m	А		
* OR Area	FHA	<i>m</i> ²		* OR Area	SPA	<i>m</i> ²			

Measurement source:A=Authenticated;O=Owner measured;S=Sister vessel;P=Published;C=CalculatedSystem data source:D=Database derived;E=EstimatedTCC calculated on 15/05/2024 at 07:46:30

IMPORTANT: see notes on page 2 for appropriate use and validity

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail. For boats without a downwind headsail the words "(no downwind H/S)" appear after the TCC.

Boats with a full sailplan also have a "TCC 2" which excludes all downwind headsails. Strictly this is for use only when racing in a class specifically for boats without downwind headsails..

If boats with and without downwind headsails race together, the boats without downwind sails will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

5. Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted	Yes	
Dayboat	No	
SSS base value	38	Valid only for data on this certificate.