## STONEWAYS VPRS

# Rating Certificate

Yacht	Cloud 9	Rig	Bermudian Sloop
Sail number	GBR5843L	Design	Hanse 348
TCC	0.921	Series / built	2018 / 2019
No spinnaker TCC	0.890	Crew limit	8 people

_			
Dort	ormance	Inc	licatore
ГСП	Ulliance	1110	iicatoi 5

Mainsail area	<b>34.50</b> m <sup>2</sup>	Mizzen / mizzen staysail area	<b>0.00</b> r	m² /	<b>0.00</b> m <sup>2</sup>
Upwind headsail area	<b>22.99</b> m <sup>2</sup>	Displacement / length	214		
Flying headsail area	<b>60.30</b> m <sup>2</sup>	Sail area / wetted surface	<b>2.10</b> (	upwind sails	)
Spinnaker area	<b>0.00</b> $m^2$	Sail area / displacement	<b>15.73</b> (	upwind sails	)

Hull & appendages			source
Hull Length	LH	<b>9.99</b> m	P
Bow overhang	ВО	<b>0.07</b> m	D
Stern overhang	SO	<b>0.36</b> m	D
Waterline length	LWL	<b>9.56</b> m	C
Stern height	Y	<b>0.08</b> m	D
Beam	MB	<b>3.51</b> m	D
Topside overhang	TSO	<b>0.31</b> m	D
Freeboard at mast	FBI	<b>1.20</b> m	D
Draught	T	<b>1.95</b> m	P
Empty weight	EW	<b>6200</b> kg	P
Fixed ballast weight	KW	<b>2030</b> kg	P
Moveable ballast		None	
Keel type		H2H5R1N1	
Keel depth	KD	<b>1.45</b> m	D
Keel chord	KC	<b>1.09</b> m	D
Rudder type		Spade	
Rudder depth	RD	<b>1.74</b> m	D
Rudder chord	RC	<b>0.53</b> m	D
Propeller type		Folding	
Propeller blades	PRN	2	
Propeller diameter	PRD	<b>0.38</b> m	E
Mizzen stavsail			

	***			= 0 11 0 1 0 1 1 1 1 1 1
D	m	0.36	SO	Stern overhang
C	m	9.56	LWL	Waterline length
D	m	0.08	Y	Stern height
D	m	3.51	MB	Beam
D	m	0.31	TSO	Topside overhang
D	m	1.20	FBI	Freeboard at mast
P	m	1.95	T	Draught
P	kg	6200	EW	Empty weight
P	kg	2030	KW	Fixed ballast weight
	)	None		Moveable ballast
	R1N1	H2H5		Keel type
D	m	1.45	KD	Keel depth
D	m	1.09	KC	Keel chord
	e	Spade		Rudder type
D	m	1.74	RD	Rudder depth
D	m	0.53	RC	Rudder chord
	ng	Foldi		Propeller type
		2	PRN	Propeller blades
Ε	m	0.38	PRD	Propeller diameter

Mizzen staysail			
Staysail luff length	LLY	m	
Staysail luff perp LPY m			
Flying headsail			

Flying headsa	il			
FH lu	ıff length	FHLU	т	
FH leech length		FHLE	m	
FH half width		FHHW	m	
FH foot width		FHFL	m	
* OR	Area	FHA	<b>60.30</b> m <sup>2</sup>	0

Rig			source
Spar material		Alumini	um alloy
Forestay length	FL	<b>14.30</b> m	E
Foretriangle base	J	<b>3.88</b> m	P
Flying h/sail tack length	FHTL	<b>4.28</b> m	P
Spinnaker pole length	SPL	m	P
Mainsail hoist	P	<b>13.10</b> m	P
Mainsail outhaul	E	<b>4.40</b> m	P
Boom above sheer	BAS	<b>1.95</b> m	D
Mizzen hoist	PY	m	
Mizzen outhaul	FY	m	

Main sail			
Half width	MHW	<b>2.88</b> m	Р
Three quarter width	MTW	<b>1.74</b> m	P
Upper width	MUW	<b>1.02</b> m	P
Construction		Woven	
Reefing		Slab	
9			

Upwind headsail			
Luff length	HLU	<b>14.02</b> m	Ε
Luff perpendicular	HLP	<b>3.28</b> m	P
Half width	HHW	<b>1.64</b> m	Ε
Three quarter width	HTW	<b>0.82</b> m	Ε
Foot height	HFH	<b>0.25</b> m	E
Construction		Woven	
Reefing		Roller	

Spinnaker				
* Lu	ıff length	SLU	т	
* Leech length		SLE	m	
* Half width		SHW	m	
* Foot width		SFL	m	
* OR	Area	SPA	m²	

*Measurement source*: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated System data source: D=Database derived; E=Estimated TCC calculated on 09/01/2024 at 13:32:43

IMPORTANT: see notes on page 2 for appropriate use and validity

### Certificate notes

#### 1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

#### 2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

#### 3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

#### 4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

#### Additional information

#### 6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

**SSS base value** 41 Valid only for data on this certificate.