STONEWAYS VPRS

2024 Rating Certificate

Yacht	Maestrale IV			Rig	Bermudian Sloop			
Sail number	BRA280	05		Design		Felci 315		
TCC	0.996			Series / built		/ 2022		
No spinnaker TCC	0.946			Crew limit	8	people		
· .						 		
Performance indicator		2	N.A.		0.00 /	2 ,	0.00 2	
Mainsail area	31.41 m ²		IVII	Mizzen / mizzen staysail area		m² /	0.00 m ²	
Upwind headsail area	25.91 m ²		Displacement / length		173			
Flying headsail area	84.37 m ²		Sail area / wetted surface		2.62 (upwind sails)			
Spinnaker area	81.11 n	n ²		Sail area / displacement	21.23	(upwind sails)		
Hull & appendages			source	Rig			source	
Hull Length	LH	9.50 m	D	Spar material		Aluminiun	n alloy	
Bow overhang	ВО	0.09 m	Α	Forestay length	FL	13.26 m	Α	
Stern overhang	SO	0.61 m	Α	Foretriangle base	J	3.66 m	Α	
Waterline length	LWL	8.80 m	С	Flying h/sail tack length	FHTL	4.66 m	Α	
Stern height	Y	0.14 m	Α	Spinnaker pole length	SPL	4.15 m	Α	
Beam	MB	3.24 m	D	Mainsail hoist	P	12.45 m	Α	
Topside overhang	TSO	0.26 m	D	Mainsail outhaul	E	4.25 m	Α	
Freeboard at mast	FBI	1.03 m	D	Boom above sheer	BAS	1.41 m	Α	
Draught	T	2.06 m	D	Mizzen hoist	PY	m		
Empty weight	EW	3725 kg	Α	Mizzen outhaul	EY	т		
Fixed ballast weight	KW	1392 kg	E	Main sail				
Moveable ballast		None		Half width	MHW	2.77 m	Α	
Keel type		R3R1R2N1		Three quarter width	MTW	1.64 m	Α	
Keel depth	KD	1.71 m	Α	Upper width	MUW	0.91 m	Α	
Keel chord	KC	0.64 m	Α	Construction		Laminated	1	
Rudder type		Spade		Reefing		Slab		
Rudder depth	RD	1.51 m	Α	Upwind headsail				
Rudder chord	RC	0.37 m	Α	Luff length	HLU	12.67 m	Α	
Propeller type		Folding		Luff perpendicular	HLP	3.83 m	Α	
Propeller blades	PRN	2		Half width	HHW	2.12 m	Α	
Propeller diameter	PRD	0.39 m	Α	Three quarter width	HTW	1.17 m	Α	
Mizzen staysail				Foot height	HFH	0.10 m	Е	
Staysail luff length	LLY	m		Construction		Laminated	1	
Staysail luff perp	LPY	m		Reefing		Change Sa	ail	
Flying headsail				Spinnaker				
FH luff length	FHLU	14.61 m	Α	* Luff length	SLU	13.49 m	Α	
FH leech length	FHLE	13.02 m	Α	* Leech length	SLE	13.49 m	Α	
FH half width	FHHW	7.54 m	Α	* Half width	SHW	7.28 m	Α	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source:** D=Database derived; E=Estimated **TCC calculated** on 12/01/2024 at 07:34:38

* OR ...

Area

SPA

IMPORTANT: see notes on page 2 for appropriate use and validity

84.37 m²

FH foot width FHFL
* OR ... Area FHA

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 22 Valid only for data on this certificate.