STONEWAYS VPRS

2024 Rating Certificate

Yacht	Sweet Martini			Rig	Bermudian Sloop		
Sail number	IRL501	3		Design	SHE 3	1	
TCC		no downwind	H/S)	Series / built	1969	/ 1973	
TCC 2	01700	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	a : 1, 0,	Crew limit	7	people	
				Olew IIIIII		реоріе	
Performance indicators							
Mainsail area	18.42		Mi	zzen / mizzen staysail area	0.00	m^2 /	0.00 m ²
Upwind headsail area	24.59 ₁			Displacement / length	334		
Flying headsail area	0.00 1	m^2		Sail area / wetted surface	2.34	(upwind sails)	
Spinnaker area	0.00 ₁	m^2		Sail area / displacement	16.82	(upwind sails)	
Hull & appendages			source	Rig			source
Hull Length	LH	9.33 m	D	Spar material		Aluminiur	n alloy
Bow overhang	BO	1.31 m	E	Forestay length	FL	10.70 m	Ε
Stern overhang	SO	1.24 m	E	Foretriangle base	J	3.48 m	P
Waterline length	LWL	6.78 m	С	Flying h/sail tack length	FHTL	т	P
Stern height	Y	0.35 m	E	Spinnaker pole length	SPL	т	P
Beam	MB	2.68 m	D	Mainsail hoist	P	10.45 m	P
Topside overhang	TSO	0.16 m	D	Mainsail outhaul	E	3.05 m	P
Freeboard at mast	FBI	1.06 m	E	Boom above sheer	BAS	0.90 m	E
Draught	T	1.68 m	P	Mizzen hoist	PY	т	
Empty weight	EW	3538 kg	P	Mizzen outhaul	EY	т	
Fixed ballast weight	KW	1550 kg	P	Main sail			
Moveable ballast		None		Half width	MHW	1.90 m	0
Keel type		T1H3R1N1		Three quarter width	MTW	1.11 m	0
Keel depth	KD	1.01 m	S	Upper width	MUW	0.64 m	0
Keel chord	KC	1.42 m	S	Construction		Woven	
Rudder type		Skeg hung		Reefing		Slab	
Rudder depth	RD	1.08 m	0	Upwind headsail			
Rudder chord	RC	0.71 m	0	Luff length	HLU	10.52 m	0
Propeller type		Fixed		Luff perpendicular	HLP	4.88 m	0
Propeller blades	PRN	3		Half width	HHW	2.26 m	0
Propeller diameter	PRD	0.35 m	0	Three quarter width	HTW	1.08 m	0
Mizzen staysail				Foot height	HFH	0.25 m	Е
Staysail luff length	LLY	т		Construction		Woven	
Staysail luff perp	LPY	m		Reefing		Roller	
Flying headsail (down	Spinnaker (downwind	headsai	l)				
FH luff length	FHLU	m		* Luff length	SLU	т	
FH leech length	FHLE	m		* Leech length	SLE	т	
FH half width	FHHW	m		* Half width	SHW	т	
FH foot width	FHFL	m		* Foot width	SFL	m	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated **System data source:** D=Database derived; E=Estimated TCC calculated on 28/03/2024 at 15:05:29

* OR ...

SPA

IMPORTANT: see notes on page 2 for appropriate use and validity

* OR ... Area FHA

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail. For boats without a downwind headsail the words "(no downwind H/S)" appear after the TCC.

Boats with a full sailplan also have a "TCC 2" which excludes all downwind headsails. Strictly this is for use only when racing in a class specifically for boats without downwind headsails.

If boats with and without downwind headsails race together, the boats without downwind sails will have an advantage on upwind legs, and a disadvantage off the wind.

Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 29 Valid only for data on this certificate.