STONEWAYS VPRS

Rating Certificate

Yacht	The Great Escape	Rig	Bermudian Sloop
Sail number	IRL1217	Design	Bavaria 33 Cruiser
TCC	0.859 (no downwind H/S)	Series / built	2005 / 2006
TCC 2		Crew limit	9 people
Performance indicator	s		

Performance	indicators
--------------------	------------

Mainsail area	24.45 m ²	Mizzen / mizzen staysail area	0.00	m^2 /	0.00 m ²
Upwind headsail area	29.06 m ²	Displacement / length	220		
Flying headsail area	0.00 m ²	Sail area / wetted surface	2.16	(upwind sails)	
Spinnaker area	0.00 m^2	Sail area / displacement	15.90	(upwind sails)	

Hull & appendages			source
Hull Length	LH	10.45 m	P
Bow overhang	ВО	0.44 m	E
Stern overhang	SO	1.09 m	E
Waterline length	LWL	9.00 m	P
Stern height	Y	0.15 m	0
Beam	MB	3.48 m	P
Topside overhang	TSO	0.29 m	E
Freeboard at mast	FBI	1.07 m	E
Draught	T	1.50 m	P
Empty weight	EW	5400 kg	P
Fixed ballast weight	KW	1450 kg	P
Moveable ballast			
Keel type		H2H5R2N1	
Keel depth	KD	0.97 m	E
Keel chord	KC	1.30 m	E
Rudder type		Spade	
Rudder depth	RD	1.40 m	E
Rudder chord	RC	0.45 m	E
Propeller type		Fixed	
Propeller blades	PRN	2	
Propeller diameter	PRD	0.38 m	Ε

Bow overhang	ВО	0.44 n	n E
Stern overhang	SO	1.09 n	n E
Waterline length	LWL	9.00 n	n P
Stern height	Y	0.15 n	1 0
Beam	MB	3.48 n	n P
Topside overhang	TSO	0.29 n	n E
Freeboard at mast	FBI	1.07 n	n E
Draught	T	1.50 n	n P
Empty weight	EW	5400 k	g P
Fixed ballast weight	KW	1450 k	g P
Moveable ballast			
Keel type		H2H5R	2N1
Keel depth	KD	0.97 n	n E
Keel chord	KC	1.30 n	n E
Rudder type		Spade	
Rudder depth	RD	1.40 n	n E
Rudder chord	RC	0.45 n	n E
Propeller type		Fixed	
Propeller blades	PRN	2	
Propeller diameter	PRD	0.38 n	n E

Mizzen staysail			
Staysail luff length	LLY	m	
Stavsail luff perp	LPY	m	

riyilig neausa	ii (aowiiv	villa neads	ali)	
FH lu	ff length	FHLU	т	
FH leed	h length	FHLE	m	
FH h	alf width	FHHW	m	
FH fo	oot width	FHFL	m	
* OR	Area	FHA	m²	

Rig			source
Spar material		Alumin	ium alloy
Forestay length	FL	13.25 m	0
Foretriangle base	J	3.70 m	n D
Flying h/sail tack length	FHTL	n	n D
Spinnaker pole length	SPL	n	n D
Mainsail hoist	P	11.95 m	n D
Mainsail outhaul	E	4.25 m	n D
Boom above sheer	BAS	1.50 m	n D
Mizzen hoist	PY	m	1
Mizzen outhaul	FY	n	7

Main sail			
Half width	MHW	1.97 m	0
Three quarter width	MTW	0.97 m	0
Upper width	MUW	0.50 m	0
Construction		Woven	
Reefing		In-mast	

Upwind headsail			
Luff length	HLU	12.11 m	0
Luff perpendicular	HLP	4.98 m	0
Half width	HHW	2.32 m	0
Three quarter width	HTW	1.14 m	0
Foot height	HFH	0.30 m	E
Construction		Woven	
Reefing		Roller	

	Reeling		Holler	
Spinnaker (do	wnwind h	eadsail)		
* Lı	uff length	SLU	m	
* Lee	ch length	SLE	m	
* H	lalf width	SHW	m	
* F	oot width	SFL	m	
* OR	Area	SPA	m^2	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated System data source: D=Database derived; E=Estimated TCC calculated on 26/03/2024 at 08:39:22

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail. For boats without a downwind headsail the words "(no downwind H/S)" appear after the TCC.

Boats with a full sailplan also have a "TCC 2" which excludes all downwind headsails. Strictly this is for use only when racing in a class specifically for boats without downwind headsails.

If boats with and without downwind headsails race together, the boats without downwind sails will have an advantage on upwind legs, and a disadvantage off the wind.

Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted No

Dayboat No

SSS base value 29 Valid only for data on this certificate.