STONEWAYS VPRS

2024 Rating Certificate

Yacht	White Magic				Rig	Bermi	udian Sloop	
Sail number	GBR8872			Design		Hunter Sonata		
TCC	0.813	_			Series / built	1976		
No spinnaker TCC	0.798				Crew limit	5	people	
·					Olew minit		реоріе	
Performance indicators							0	0
Mainsail area	12.89 n	-		Miz	zzen / mizzen staysail area	0.00	m² /	0.00 m ²
Upwind headsail area	13.67 n				Displacement / length	249		
Flying headsail area	0.00 n				Sail area / wetted surface		(upwind sails)	
Spinnaker area	26.91 n	1 ²			Sail area / displacement	19.39	(upwind sails)	
Hull & appendages			soul	rce	Rig			source
Hull Length	LH	6.55	m A	1	Spar material		Aluminiui	n alloy
Bow overhang	ВО	0.69	m [Forestay length	FL	7.81 m	D
Stern overhang	SO	0.33	m L		Foretriangle base	J	2.45 m	D
Waterline length	LWL	<i>5.53</i>	m (Flying h/sail tack length	FHTL	m	D
Stern height	Y	0.15	m L		Spinnaker pole length	SPL	2.44 m	D
Beam	MB	2.59	m F		Mainsail hoist	P	7.93 m	P
Topside overhang	TSO	0.30	m L		Mainsail outhaul	E	2.59 m	P
Freeboard at mast	FBI	0.85	m S	3	Boom above sheer	BAS	0.79 m	E
Draught	T	1.40	m F	,	Mizzen hoist	PY	т	
Empty weight	EW	1220	kg A	١	Mizzen outhaul	EY	т	
Fixed ballast weight	KW	450	kg F	,	Main sail			
Moveable ballast		None			Half width	MHW	1.84 m	P
Keel type		Z2P1F	R1N1		Three quarter width	MTW	1.11 m	P
Keel depth	KD	1.06	m S	3	Upper width	MUW	0.64 m	Ε
Keel chord	KC	0.76	m S	3	Construction		Woven	
Rudder type	Transom-hung				Reefing		Slab	
Rudder depth	RD	0.84	m F	,	Upwind headsail			
Rudder chord	RC	0.35	m F	,	Luff length	HLU	7.47 m	P
Propeller type		None			Luff perpendicular	HLP	3.66 m	P
Propeller blades	PRN				Half width	HHW	1.83 m	E
Propeller diameter	PRD		m		Three quarter width	HTW	0.92 m	E
Mizzen staysail					Foot height	HFH	0.00 m	E
Staysail luff length	LLY		m		Construction		Laminated	d
Staysail luff perp	LPY		m		Reefing		Change S	ail
Flying headsail					Spinnaker			
FH luff length	FHLU		m		* Luff length	SLU	7.42 m	P
FH leech length	FHLE		m		* Leech length	SLE	7.42 m	P
FH half width	FHHW		m		* Half width	SHW	4.37 m	P
FH foot width	FHFL		m		* Foot width	SFL	4.37 m	P

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated

System data source: D=Database derived; E=Estimated

TCC calculated on 15/01/2024 at 09:57:44

* OR ...

SPA

IMPORTANT: see notes on page 2 for appropriate use and validity

Area

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted Yes

Dayboat No

SSS base value 7 Valid only for data on this certificate.