

Yacht	Yapluka	Rig	Bermudian Sloop
Sail number	GBR5258L	Design	RM 1070
TCC	1.012	Series / built	
No spinnaker TCC	0.961	Default crew limit	10 people

Performance indicators

Mainsail area	37.30 m²	Sailing weight	6631 kg
Mizzen area	m²	Displacement / length	153 (sailing weight)
Upwind headsail area	38.31 m²	Sail area / wetted surface	2.64 (main + u/w headsail)
D/wind headsail area	110.44 m²	Sail area / displacement	21.77 (main + u/w headsail)

Hull

source

Hull Length	LH	10.69 m	P
Bow overhang	BO	0.00 m	E
Stern overhang	SO	0.19 m	E
Waterline length	LWL	10.50 m	C
Stern height	Y	0.05 m	E
Beam	MB	4.00 m	P
Topside overhang	TSO	0.40 m	E
Freeboard at mast	FBI	1.30 m	E
Draught	T	1.72 m	P
Empty weight	EW	5604 kg	P
Fixed ballast weight	KW	1800 kg	P
Moveable ballast		None	

Rig

source

Spar material		Aluminium alloy	
Forestay length	FL	15.98 m	E
Foretriangle base	J	4.26 m	P
Mainsail hoist	P	14.31 m	P
Mainsail outhaul	E	4.56 m	P

Main sail

Half width	MHW	2.81 m	A
Three quarter width	MTW	1.61 m	A
Upper width	MUW	0.89 m	A
Construction		Laminated	
Reefing		Slab	

Upwind headsail

Luff length	HLU	14.95 m	A
Luff perpendicular	HLP	5.22 m	A
Half width	HHW	2.50 m	A
Three quarter width	HTW	1.28 m	A
Foot height	HFH	0.25 m	E
Construction		Woven	
Reefing		Change Sail	

Downwind headsail

Tack type		Bow sprit	
Pole / tack length	STL	5.30 m	E
* Luff length	SLU	16.29 m	A
* Leech length	SLE	14.90 m	A
* Half width	SHW	8.49 m	A
* Foot width	SFL	8.70 m	A
* OR ... Area	SPA	m²	

Appendages & propeller

Keel type		R2B3R1N1	
Keel depth	KD	1.42 m	O
Keel chord	KC	0.65 m	O
Rudder type		Spade	
Rudder depth	RD	1.58 m	O
Rudder chord	RC	0.43 m	O
Propeller type		Feathering	
Propeller blades	PRN	3	
Propeller diameter	PRD	0.41 m	E

Mizzen

Mizzen hoist	PY	m	
Mizzen foot	EY	m	
Staysail luff length	LLY	m	
Staysail luff perp	LPY	m	

Measurement source: A=Authenticated; O=Owner measured; S=Sister vessel; P=Published; C=Calculated

System data source: D=Database derived; E=Estimated

TCC calculated on 05/05/2023 at 14:33:02

IMPORTANT: see notes on page 2 for appropriate use and validity

Certificate notes

1. Correct use of the published ratings

Multiply the elapsed time by the TCC to obtain corrected time.

The TCC is calculated for the declared sail plan, which may or may not include a downwind headsail (spinnaker). For boats without a downwind headsail the words "(no spinnaker)" appear after the TCC.

Boats with a full sailplan also have a "no spinnaker TCC" for use only when racing in a non-spinnaker class.

If spinnaker and non-spinnaker boats race together, non-spinnaker boats will have an advantage on upwind legs, and a disadvantage off the wind.

2. Data quality

The fairest ratings will result from accurate measurement; ratings calculated using a significant amount of estimated and published data are far more likely to be out of line with expectations than those using measured and sister ship data. Owners must notify the rating office of any changes or errors in the rating data.

3. Applicability

This certificate is issued for the sole purpose of correcting elapsed times recorded in yacht races. It is not to be used for any other purpose.

4. Validity

Unless stated to the contrary, or superseded, this certificate is valid until the end of the calendar year in which it was issued. The validity can be checked by referring to the certificates published at: www.vprs.org/ratings.html

5. Additional information

6. Stability

An SSS base value provides a guide to the stability of a boat but does not guarantee safety or freedom of risk from capsize or sinking. The safety of a boat is the sole responsibility of the skipper who must ensure that the boat is fully found, thoroughly seaworthy, and operated by a crew sufficient in number and experience who are physically fit to face bad weather. The SSS base value does not constitute any warranty as to the seaworthiness of any boat or the safety of any gear and shall not limit the absolute responsibility of the skipper of the boat.

Guard rails fitted	Yes	
Dayboat	No	
SSS base value	29	Valid only for data on this certificate.